

View Online at <https://aerobasegroup.com/nsn/9540-01-217-4126>

Fabrication Method:

Extruded

Overall Height:

1.750 inches

Length:

Between 10.000 feet and 12.000 feet

Left Side Top Flange Thickness:

0.094 inches

Right Side Top Flange Thickness:

0.094 inches

Basic Shape Style:

T shape

First Tip Radius:

0.094 inches

Leg Thickness:

0.094 inches

Left Side Top Flange Distance To Center Of Both Flanges:

0.922 inches

Right Side Top Flange Distance To Center Of Both Flanges:

0.953 inches

Fillet Radius Where Top Left Flange Joins Web Flange/leg:

0.125 inches

Fillet Radius Where Top Right Flange Joins Web Flange/leg:

0.125 inches

Top Flange Width:

1.875 inches

First Tip Style:

Lower radius

Third Tip Radius:

0.047 inches

Second Tip Relationship To First Tip:

Identical

Third Tip Relationship To Preceding Tips:

Not identical

Third Tip Style:

Full radius

Right Top Inside Angle:

90.0 degrees

Left Top Inside Angle:

90.0 degrees

Heat Treatment:

T-76511 solution heat treated

Material:

Aluminum alloy ams-qq-a-200/15, alloy 7075

Material:

Aluminum alloy ams-qq-a-200/15, alloy 7075

Specification Data:

80205-nas344 professional/industrial association standard

Specification Or Standard:

T76511 temper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A13100