NSN 9540-01-229-8320

Structural Beam - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/9540-01-229-8320

Fabrication Method:

Extruded

Overall Height:

Between 1.160 inches and 1.184 inches

Length:

Between 10.000 feet and 12.000 feet

Left Side Top Flange Thickness:

Between 0.110 inches and 0.122 inches

Right Side Top Flange Thickness:

Between 0.110 inches and 0.122 inches

Basic Shape Style:

T shape

Leg Thickness:

Between 0.059 inches and 0.071 inches

Left Side Top Flange Distance To Center Of Both Flanges:

Between 1.854 inches and 1.886 inches

Right Side Top Flange Distance To Center Of Both Flanges:

Between 1.854 inches and 1.886 inches

Fillet Radius Where Top Left Flange Joins Web Flange/leg:

Between 0.084 inches and 0.116 inches

Fillet Radius Where Top Right Flange Joins Web Flange/leg:

Between 0.084 inches and 0.116 inches

Top Flange Width:

Between 3.776 inches and 3.824 inches

Weight Per Unit Measure:

0.638 pounds per linear foot

First Tip Style:

Square end

Second Tip Relationship To First Tip:

Identical

Third Tip Relationship To Preceding Tips:

Identical w/first tip

Right Top Inside Angle:

90.0 degrees

Left Top Inside Angle:

90.0 degrees

Special Features:

Flange one side of ctr leg, 0.332 in. Lg, 90.0 degrees angle

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy ams-qq-a-200/11, alloy 7075

NSN 9540-01-229-8320

Structural Beam - Page 2 of 2



ate		

Aluminum alloy ams-qq-a-200/11, alloy 7075

Specification Or Standard:

7075 alloy and t6 temper

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A13100