NSN 9540-01-229-8320

Structural Beam - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/9540-01-229-8320



Fabrication Method: Extruded **Overall Height:** Between 1.160 inches and 1.184 inches Length: Between 10.000 feet and 12.000 feet Left Side Top Flange Thickness: Between 0.110 inches and 0.122 inches **Right Side Top Flange Thickness:** Between 0.110 inches and 0.122 inches **Basic Shape Style:** T shape Leg Thickness: Between 0.059 inches and 0.071 inches Left Side Top Flange Distance To Center Of Both Flanges: Between 1.854 inches and 1.886 inches **Right Side Top Flange Distance To Center Of Both Flanges:** Between 1.854 inches and 1.886 inches Fillet Radius Where Top Left Flange Joins Web Flange/leg: Between 0.084 inches and 0.116 inches Fillet Radius Where Top Right Flange Joins Web Flange/leg: Between 0.084 inches and 0.116 inches **Top Flange Width:** Between 3.776 inches and 3.824 inches Weight Per Unit Measure: 0.638 pounds per linear foot First Tip Style: Square end Second Tip Relationship To First Tip: Identical Third Tip Relationship To Preceding Tips: Identical w/first tip **Right Top Inside Angle:** 90.0 degrees Left Top Inside Angle: 90.0 degrees **Special Features:** Flange one side of ctr leg, 0.332 in. Lg, 90.0 degrees angle **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy ams-qq-a-200/11, alloy 7075

NSN 9540-01-229-8320

Structural Beam - Page 2 of 2



Material:

Aluminum alloy ams-qq-a-200/11, alloy 7075

Specification Or Standard:

7075 alloy and t6 temper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A13100