

View Online at <https://aerobasegroup.com/nsn/9540-01-358-7367>

Fabrication Method:

Extruded

Overall Height:

0.750 inches

Length:

Between 10.000 feet and 12.000 feet

Left Side Top Flange Thickness:

0.094 inches

Right Side Top Flange Thickness:

0.094 inches

Basic Shape Style:

T shape

First Tip Radius:

0.094 inches

Leg Thickness:

0.094 inches

Left Side Top Flange Distance To Center Of Both Flanges:

0.625 inches

Right Side Top Flange Distance To Center Of Both Flanges:

0.625 inches

Fillet Radius Where Top Left Flange Joins Web Flange/leg:

0.125 inches

Fillet Radius Where Top Right Flange Joins Web Flange/leg:

0.125 inches

Top Flange Width:

1.250 inches

Weight Per Unit Measure:

0.152 pounds per linear foot

First Tip Style:

Lower radius

Third Tip Radius:

0.047 inches

Second Tip Relationship To First Tip:

Identical

Third Tip Relationship To Preceding Tips:

Not identical

Third Tip Style:

Full radius

Right Top Inside Angle:

90.0 degrees

Left Top Inside Angle:

90.0 degrees

Heat Treatment:

T-6511 solution heat treated

Material:

Aluminum alloy, qq-a-200/8 or aluminum alloy, qq-a-200/16, alloy 6061

Material:

Aluminum alloy 6061 or aluminum alloy 6062 or aluminum alloy, qq-a-200/16, alloy 6061

Material Specification:

Qq-a-200/8 federal specification 1st material response

Specification Or Standard:

T6511 temper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A13100