

View Online at <https://aerobasegroup.com/nsn/9540-01-363-7434>

**Fabrication Method:**

Extruded

**Overall Height:**

1.125 inches

**Length:**

Between 10.000 feet and 12.000 feet

**Left Side Top Flange Thickness:**

0.094 inches

**Right Side Top Flange Thickness:**

0.094 inches

**Basic Shape Style:**

T shape

**First Tip Radius:**

0.094 inches

**Leg Thickness:**

0.094 inches

**Left Side Top Flange Distance To Center Of Both Flanges:**

1.125 inches

**Right Side Top Flange Distance To Center Of Both Flanges:**

1.125 inches

**Fillet Radius Where Top Left Flange Joins Web Flange/leg:**

0.125 inches

**Fillet Radius Where Top Right Flange Joins Web Flange/leg:**

0.125 inches

**Top Flange Width:**

2.250 inches

**Weight Per Unit Measure:**

0.372 pounds per linear foot

**First Tip Style:**

Lower radius

**Third Tip Radius:**

0.047 inches

**Second Tip Relationship To First Tip:**

Identical

**Third Tip Relationship To Preceding Tips:**

Not identical

**Third Tip Style:**

Full radius

**Right Top Inside Angle:**

90.0 degrees

**Left Top Inside Angle:**

90.0 degrees

**Heat Treatment:**

O-annealed

**Material:**

Aluminum alloy ams-qq-a-200/11, alloy 7075

**Material:**

Aluminum alloy ams-qq-a-200/11, alloy 7075

**Specification Data:**

80205-nas344 professional/industrial association standard

**Specification Or Standard:**

Alloy 7075 and condition annealed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A13100