

View Online at <https://aerobasegroup.com/nsn/9905-00-846-4521>

Width:

Between 6.375 inches and 6.625 inches

Thickness:

0.032 inches

Length:

Between 13.125 inches and 13.375 inches

Attachment Method:

Hole

Environmental Protection:

Corrosion resistant and nonphenolic grease solvent and thermal shock resistant and weather resistant

Basic Shape Style:

Rectangular

Marking Designation:

Legend 1st side

Inscription:

1st inscription: partial legend, vehicle operation normal starting 1. Place gear selector in n /neutral/. 2. Push start button to turn over engine with ignite; 2nd inscription: partial legend, water operation before entering water' 1. Visually check' three bottom drain plugs, two rear hull drain plugs and two final; 3rd inscription: partial legend, towed or push start 1. Place gear shift in neutral. Tow or push vehicle at 10-15 mph. 2. Place gear shift lever in 3-6 range; 4th inscription: partial legend, parking 1. Return gear selector to neutral. 2. Apply both differential brakes and depress thumb buttons to lock levers in fu 1st side

Color:

White inscription

Material:

Aluminum alloy

Material Specification:

Qq-a-250/1, alloy 1100, h12 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 1 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528w0

Mil-std (military Standard):

Mil-a-8625 spec.