

View Online at <https://aerobasegroup.com/nsn/9905-00-930-8939>

**Width:**

22.000 inches

**Thickness:**

0.030 inches

**Length:**

5.250 inches

**Attachment Method:**

Hole

**Environmental Protection:**

Corrosion resistant and nonphenolic grease solvent and thermal shock resistant and weather resistant

**Basic Shape Style:**

Rectangular

**Marking Designation:**

Legend

**Inscription:**

1st inscription: partial legend, warning, for safe water operation vehicle should trim level side to side. Level trim is obtained by, 1. Adding sufficient ball; 2nd inscription: partial legend, one or two sets pl@s, an/grc-3 12, an/grc-4 13, an/grc-7 12, an/vrc-47 14, an/uic-1 an/vrq-1 11, an/uic-1 an/vrq-3 12, an/vic-1 an/; 3rd inscription: partial legend, three sets pl@s, an/uic-1 an/vrq-1 an/grc-19 8, an/uic-1 an/vrq-1 an/vrc-29 3, an/uic-1 an/vrq-3 an/grc-19 8, an/uic-1 an/vrq-3; 4th inscription: partial legend, four or more sets pl@s, an/uic-1 an/vrq-1 an/grr-5 an/grc-19 6, an/uic-1 an/vrq-1 an/grr-5 an/vrc-24 9, an/uic-1 an/vrq-3 an/gr 1st side

**Color:**

Red inscription background

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-250/1, alloy 1100, h12 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2, class 2 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528w0

**Mil-std (military Standard):**

Mil-a-8625 spec.