

View Online at <https://aerobasegroup.com/nsn/9905-00-930-8939>

Width:

22.000 inches

Thickness:

0.030 inches

Length:

5.250 inches

Attachment Method:

Hole

Environmental Protection:

Corrosion resistant and nonphenolic grease solvent and thermal shock resistant and weather resistant

Basic Shape Style:

Rectangular

Marking Designation:

Legend

Inscription:

1st inscription: partial legend, warning, for safe water operation vehicle should trim level side to side. Level trim is obtained by, 1. Adding sufficient ball; 2nd inscription: partial legend, one or two sets pl@s, an/grc-3 12, an/grc-4 13, an/grc-7 12, an/vrc-47 14, an/uic-1 an/vrq-1 11, an/uic-1 an/vrq-3 12, an/vic-1 an/; 3rd inscription: partial legend, three sets pl@s, an/uic-1 an/vrq-1 an/grc-19 8, an/uic-1 an/vrq-1 an/vrc-29 3, an/uic-1 an/vrq-3 an/grc-19 8, an/uic-1 an/vrq-3; 4th inscription: partial legend, four or more sets pl@s, an/uic-1 an/vrq-1 an/grr-5 an/grc-19 6, an/uic-1 an/vrq-1 an/grr-5 an/vrc-24 9, an/uic-1 an/vrq-3 an/gr 1st side

Color:

Red inscription background

Material:

Aluminum alloy

Material Specification:

Qq-a-250/1, alloy 1100, h12 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528w0

Mil-std (military Standard):

Mil-a-8625 spec.